INDEX OF SHEETS

SHEET NO.	DESCRIPTION	STATE STANDARDS	
1	TITLE SHEET	000001- <i>05</i>	STANDARD SYMBOLS, ABBREVIATIONS, AND PATTERNS
2	INDEX OF SHEETS, STATE STANDARDS AND GENERAL NOTES	606001 <i>-03</i>	CONCRETE CURB TYPE B AND COMBINATION CONCRETE CURB AND GUTTER
^{-∜} 3	SUMMARY OF QUANTITIES	701400 <i>-0</i> 2	APPROACH TO LANE CLOSURE FREEWAY/EXPRESSWAY
4	ALIGNMENT AND CONTROL POINTS	701406 <i>-04</i>	LANE CLOSURE, FREEWAY/EXPRESSWAY, DAY OPERATION ONLY
5	TYPICAL SECTIONS	701901 <i>430001</i>	TRAFFIC CONTROL DEVICES
6	PROPOSED ROADWAY PLAN		
7	ROADWAY PROFILE		
8	PAVEMENT MARKING PLAN		
9	MAINTENANCE OF TRAFFIC (DETOUR PLAN)		
10-11	CROSS SECTIONS		
12	CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT (BD-24)		
13	BUTT JOINT AND HMA TAPER DETAILS (BD-32)		
14	FREEWAY ENTRANCE AND EXIT RAMP CLOSURE DETAILS (TC-8)		
15-16	MULTI-LANE FREEWAY PAVEMENT MARKING DETAILS (TC-8)		
17	TRAFFIC CONTROL DETAILS FOR FREEWAY SHOULDER CLOSURES PARTIAL RAMP CLOSURES (TC-17)		
18	ARTERIAL ROAD INFORMATION SIGN (TC-22)		
18A18C.	REMOVE & RE-ERECT. STEEL PLATE BEAM GUARDRAIL DET.	AIL	

GENERAL NOTES

- BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT 800-892-0123 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE, AND GAS FACILITIES. (48 HOUR NOTIFICATIONS IS REQUIRED)
- 2. 10 FEET TRANSITIONS SHALL BE USED TO MATCH PROPOSED CURB AND GUTTER AND MEDIAN ITEMS OF WORK TO EXISTING CURBS & GUTTERS AND MEDIANS IN THE FIELD, UNLESS OTHERWISE SHOWN. THE TRANSITIONS SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE FOR THE PROPOSED ITEMS OF WORK SPECIFIED.
- 3. THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES.
- 4. THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT.
- 5. WHEN ARTIFICIAL LIGHTING IS USED IN NIGHT OPERATIONS THE CONTRACTOR SHALL EXERCISE THE UTMOST PRECAUTIONS IN PREVENTING ADVERSE VISIBILITY TO THE MOTORING PUBLIC AND ADJOINING RESIDENTIAL AREAS.
- 6. WHEN MILLED PAVEMENT IS OPENED TO TRAFFIC THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 1 1/2 INCHES WHERE THE SPEED LIMIT IS 45 MPH OR LESS AND 1 INCH WHERE THE SPEED LIMIT IS GREATER THAN 45 MPH. WITH WRITTEN APPROVAL FROM THE ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 3 INCHES MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM 3:1 (H:V).
- 7. BÛTT JOINTS WILL BE INSTALLED AT THE ENDS OF ALL RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT), IN ACCORDANCE WITH THE "BUTT JOINT AND BITUMINOUS TAPER DETAILS", UNLESS OTHERWISE SPECIFIED.
- 8. THE FOLLOWING RATES OF APPLICATION HAVE BEEN ASSUMED IN CALCULATING PLAN

BITUMINOUS MATERIALS (PRIME COAT)

0.0004 TONS/SQ YD

HOT-MIX ASPHALT SURFACE COURSE

112 LBS/SQ YD/INCH

Ciorba Group, Inc.

CONSULTING ENGINEERS

5507 North Cumberland Avenue, Suite 402
Chicago, Illinois 60856
Tel. 773.775.4000

Fax 773.775.4014

PLOT DATE = 18/25/2807

DESIGNED - WBL REVISED -REVISED PLOT SCALE = 0.9799 '/ IN. CHECKED - MJL REVISED DATE 9/19/2007 REVISED

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION**

FAP ROUTE 347 SECTION **ILLINOIS ROUTE 38** (C&J) R-RS-2 INDEX OF SHEETS, STATE STANDARDS & GENERAL NOTES SCALE: NO SCALE SHEET NO. 1 OF 1 SHEETS STA.

TOTAL SHEE SHEETS NO.

COUNTY DU PAGE 18 2 CONTRACT NO. 60D42